

WATER DISPENSER

# AQA drink 30 & 60

## HIGH-QUALITY AND VERSATILE INDIVIDUALIST

The grid-bound AQA drink 30 and 60 captivate with their high quality and robust design in stainless steel. There are four different models to choose from, whereby each unit is equipped with up to 4 water options. Depending on individual taste you can have still, cold, sparkling or hot water at the push of a button. With a capacity of 30 l/h and 60 l/h for cold/sparkling water the units are ideal for all areas that focus on quality and performance. An integrated UVC lamp serves as a hygiene barrier from the outside at the water outlet. So that you can enjoy your daily water with hygienic safety.

### Base Cabinet

The base cabinet forms the basis of the floor-standing model of the AQA drink 30 or 60. It provides a place for the filter and the CO<sub>2</sub> bottle. In addition, an approx. 5 l waste water tank is located in the base cabinet.

### Filter technology for Magnesium Mineralized Water

The appropriate BWT AQA drink filter cartridge with patented BWT Magnesium Technology, transforms tap water into an enjoyable taste experience. For hygienic safety we recommend filters with an integrated ultrafiltration membrane that retains 99.9999% of bacteria and microplastics up to 0.001 mm.



HIGH QUALITY  
STAINLESS STEEL FINISH

UP TO 4 WATER OPTIONS





REMOVABLE  
CONTACT PROTECTION

UVC LAMP

DRIP TRAY

BWT MAGNESIUM  
FILTER TECHNOLOGY

## OVERVIEW DATA

GENERAL INFORMATION		CA		CAS		HCS		HCA	
		30	60	30	60	30	60	30	60
ARTICLE NUMBER WATER DISPENSER		825037	825036	825010	825020	825011	825021	825012	825022
ARTICLE NUMBER BASE CABINET		825028	825029	825028	825029	825028	825029	825028	825029
TYPE		tabletop/floor-standing model							
MATERIAL		stainless steel							
WATER OPTIONS		CA		CAS		HCS		HCA	
AMBIENT, STILL		✓		✓		✓		✓	
COLD, STILL		✓		✓		✓		✓	
COLD, WITH CO <sub>2</sub>		-		✓		✓		-	
HOT		-		-		✓		✓	

## TECHNICAL DATA

OPERATING CONDITIONS		CA		CAS		HCS		HCA	
		30	60	30	60	30	60	30	60
WATER DELIVERY AT ROOM TEMPERATURE, STILL	l/h	120		120		120		120	
WATER DELIVERY COLD, STILL   CO <sub>2</sub>	l/h	30   -	60   -	30   30	60   60	30   30	60   60	30   -	60   -
WATER DELIVERY HOT	l/h	-		-		8		8	
WATER TEMPERATURE COLD*	°C	~5-12		~5-12		~5-12		~5-12	
WATER TEMPERATURE HOT	°C	-		-		95		95	
FLOW SPEED	l/min	>2		>2		>2		>2	
MAX. COOLING POTENTIAL	W	100		100		100		100	
MAX. HEATING POTENTIAL	W	-		-		1.000		1.000	
PERFORMANCE COMPRESSOR	HP	1/6		1/6		1/6		1/6	
INLET WATER PRESSURE recommended   max.	bar	3   5		3   5		3   5		3   5	
CO <sub>2</sub> PRESSURE recommended   max.	bar	-		3.5   4		3.5   4		-	
COOLING TECHNOLOGY   COOLANT		dry cooling   R290							
LEAKAGE PROTECTION		yes							
CONNECTIONS		CA		CAS		HCS		HCA	
		30	60	30	60	30	60	30	60
MAINS VOLTAGE   -FREQUENCY	V   Hz	220-240   50		220-240   50		220-240   50		220-240   50	
DRINKING WATER CONNECTION	mm	8		8		8		8	
CO <sub>2</sub> CONNECTION	mm	-		8		8		-	
WASTE WATER CONNECTION/-TANK		optional							
WEIGHTS		CA		CAS		HCS		HCA	
		30	60	30	60	30	60	30	60
NET WEIGHT, WATER DISPENSER	kg	26	31	29	34	29	34	29	33
GROSS WEIGHT, WATER DISPENSER	kg	28	34	31	37	31	37	31	36
NET WEIGHT, BASE CABINET	kg	16	19	16	19	16	19	16	19
GROSS WEIGHT, BASE CABINET	kg	17	20	17	20	17	20	17	20
DIMENSIONS		AQA DRINK 30				AQA DRINK 60			
WATER DISPENSER DIMENSIONS W x H x D	cm	26 x 41.5 x 50				32 x 47 x 51			
BASE CABINET DIMENSIONS W x H x D	cm	26 x 98 x 48.5				32 x 92.5 x 48.5			
TAPPING HEIGHT	cm	28.1				32.5			

\* at 20 °C inlet temperature

PROVEN QUALITY:   RoHS



**BWT water+more GmbH**  
Walter-Simmer-Straße 4, A-5310 Mondsee

+43 (0) 800 800 555

✉ aqadrink@bwt.com

*bwt.com*